



# NITECH IPM<sup>®</sup>

NITECH INTERNATIONAL PACKAGING MACHINES

NitechIPM.com

## 77205-LPVM Low Profile Semi-Automatic Stretch Wrapper with Quick-Load Film Dispenser

If your looking for a heavy-duty, high volume, low maintenance stretch wrapper the D series is the answer. With this easy to operate machine you load the 58" variable speed turntable, attach the wrap to the load, hit the switch and walk away. The carriage raises and wraps the load until the photo electric eye senses the top of the load. When the top of the load is sensed a preset number of wraps are applied. After the number of wraps the film carriage then reverses itself and continues to wrap the load as it lowers. When it reaches the bottom, the turntable stops in the same position that it started for easy unloading. These machines with their 30%-250% Powered Brake motor stretch dispenser will save material, increase worker productivity and offer the best value for a semi-automatic wrapper.

### SPECIFICATIONS

Maximum Load Size:	56" x 56" x 80"
Production Capacity:	40 Loads Per Hour
Machine Dimensions:	85"L x 48"W x 83"H
Weight Capacity:	5,000 lbs.
Electrical Data:	120 Vac 60 Hertz 20 Amps Conventional Style 3 Prong Power Cord UL Approved Components
Turntable Size:	58" Round Steel Diamond Deck with 2" Safety Skirt
Turntable Height:	3 5/8"
Turntable Drive:	3/4 Hp Dc Motor (Totally Enclosed Fan Cooled) Variable Speed Turntable 0 to 15 RPM with Soft Start and Soft Stop 4 Point Cam Follower Turntable Supports Easy ACcess Lubrication Points on Turntable Heavy-Duty #50 Roller Chain and Drive Sprocket Synthetic Lube in all Gearboxes (-30 to 120 °F) Turntable Indexing Home Alignment
Controls:	PLC-Programmable Logic Control with Pre-Programmed Sequences Turntable Variable Speed Dial Dispenser Variable Speed Dial Film Tension Variable Dial Emergency Stop Button Photo Eye For Automatic Load Height Sensing On/Pause Button Start/Resume Switch 3 Indicator Light, Power, Ready, and Tension Liquid Crystal Display



★ MADE IN THE USA ★

Film Delivery:	Quick-Load Film Dispenser Manual Adjusted Variable Film Stretch (Load Brake) Stretch Level 30% - 150% Force to Load Accepts 12" to 20" Rolls of Stretch Film
Film Carriage:	Film Carriage Top Delay and Auto-Stop Heavy Duty Enclosed Gear Drive 76" Wrap Height (Optional Wrap Height Available) Variable Speed Carriage 0 to 20 FPM 1/4 HP 90 Volt DC Motor 12 Point UHMW Carriage Guidance Supports Dispenser Kill Switch Top / Bottom
Tower Construction:	Formed All Steel Tower 80" Wrap Height (Optional Wrap Height Available) #40 Chain Drive Lift UHMW Full Tower Slides
Frame Construction:	Custom Formed 3/8" Steel Channel All Welded Steel Construction Easy Access to all Components Forklift Portable from Front or Rear
Warranty:	3 Year Limited Warranty (100% of all Components)
Shipping Weight:	1,200 lbs.

NitechIPM  
911 23rd St. East  
Columbus, NE. 68602-1023

# 1-800-397-1100

Ph: 402-563-3188  
Fax: 402-563-2792  
NitechIPM.com

© Copyright 2013 NitechIPM. All Rights Reserved. Specifications, design, accessories or pricing without notice. Artwork does not indicate model or year and may only be reproduced with written permission from NitechIPM