



NITECH IPM[®]

NITECH INTERNATIONAL PACKAGING MACHINES

NitechIPM.com

77205-VM High Profile Semi-automatic Stretch Wrapper with Quick Load Film Dispenser

OVERVIEW

Designed for high volume stretch wrapping applications without the high price ticket. With this easy to operate machine you set the variable speed 48" round or octagon turntable, attach the wrap to the load, hit the switch and walk away. The carriage raises and wraps the load until the photo electric eye senses the top of the load. When the top of the load is sensed a preset number of wraps are applied. After the number of wraps the film carriage then reverses itself and continues to wrap the load as it lowers. When it reaches the bottom, the turntable stops in the same position that it started in for easy unloading. These machines with their 30%-225% Quick-Load film dispenser stretch feature will save material, increase worker productivity and offer the best value for a semi-automatic wrapper.

★ MADE IN THE USA ★



scale option available

SPECIFICATIONS

Maximum Load Size:	52" x 52" x 74" (120" Mast Height Available)
Production Capacity:	40 Loads Per Hour
Machine Dimensions:	85"L x 48"W x 83"H
Weight Capacity:	4,000 lbs.
Electrical Data:	120 VAC 60 Hertz 20 Amps Conventional Style 3 Prong Power Cord UL Approved Components
Turntable Size:	48" Round Steel Diamond Deck or 48" Octagon Steel Diamond Deck with 5" Safety Skirt
Turntable Height:	14 5/8"
Turntable Drive:	3/4 Hp DC Motor (Totally Enclosed Fan Cooled) Variable Speed Turntable 0 to 15 RPM with Soft Start and Soft Stop Lubrication Free Enclosed Gear Drive Design Synthetic Lube in all Gearboxes (-30 to 120 °F)
Controls:	Power On / Off With Indicator Dispenser Speed Dial Film Carriage Up / Down Controls 2 Diagnostic Lights Emergency Stop Button

Film Delivery:	Quick Load Film Dispenser Manual Adjusted Variable Film Stretch (Load Brake) Stretch Level 30% - 150% Force to Load Accepts 12" to 20" Rolls of Stretch Film
Film Carriage:	74" Wrap Height (Optional Extended Wrap Height Available) Top Over Wrap Variable Speed Carriage 0 to 20 FPM 1/4 HP 90 Volt DC Motor 12 Point UHMW Carriage Guidance Supports Dispenser Kill Switch Top / Bottom
Frame Construction:	Custom Formed 3/8" Steel Channel All Welded Steel Construction Forklift Portable from Front and Rear
Warranty:	3 Year Limited Warranty (100% of all Components)
Shipping Weight:	960 lbs.

NitechIPM
911 23rd St. East
Columbus, NE. 68602-1023

1-800-397-1100

Ph: 402-563-3188
Fax: 402-563-2792
NitechIPM.com

© Copyright 2013 NitechIPM. All Rights Reserved. Specifications, design, accessories or pricing without notice. Artwork does not indicate model or year and may only be reproduced with written permission from NitechIPM